MITEQ INC.

DASH NO.	APPLICATION		REVISIONS				
	NEXT ASSY	USED ON	LTR	DESCRIPTION		DATE	APPROVED
			E	REVISED PER ECN		04/19/11	J. Campisi

SMA FEMALE CONNECTORS (5 PLACES)

2.50
2.24
1.25

J1

MITEQ

PD4-2000/18000-30S

3.74

FREQUENCY: 2-18 GHz

S/N: XXXXXXX

.20

4.74

4.00

J2 J3 J4 J5

.40

.50   .50

∅.125
MOUNTING HOLE
(4 PLACES)

NOTES:

1. MATERIAL: ALUMINUM ALLOY 6061-T6

2. FINISH: TRIVALENT CHROMATE CONVERSION IAW:
   MIL-DTL-5541, TYPE 2, CLASS 3.

ALL PAGES ARE OF ORIGINAL ISSUE (A) EXCEPT AS NOTED.	CONTR NO. 38POD77		MITEQ 100 Davids Drive, Hauppauge, New York 11788			
	PREP BY NAME B. Davidsson	DATE 04/19/11				
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES (MM) TOLERANCES ON DECIMAL ANGLES .XX±.01 ±0°30' .XXX±.005	CHKD BY J. Campisi	05/04/11	OUTLINE DRAWING 4-WAY POWER DIVIDER PD4-2000/18000-30S			
	PROJ ENGR W. Davidsson	05/04/11				
	APPROVAL (PROJ)		SIZE A	CODE IDENT. NO. 33592	150015	
	APPROVAL (GOVT)		SCALE	REV. E	SHEET 1 OF 1	